













Lexmark XM5370

Output up to 66 ppm* and standard OCR help the Lexmark XM5370 monochrome multifunction product meet large-workgroup needs, in a size that allows flexible placement. Robust paper handling technology is designed to make printing more reliable, while long-life imaging components increase uptime and thoughtful engineering enhances serviceability.



Get more done

- Powerful 1.2-GHz guad-core processor and up to 6 GB of memory drives printing at up to 66 ppm* and scanning at up to 144 sides per minute.
- Robust paper handling includes reliable feeding of a wide range of media types and sizes and up to 3,300 sheets of input.
- Hard disk enables included OCR and enhanced scanning capabilities.
- Connect via Ethernet, USB, or simple mobile printing options.

Interact with ease

- Intuitive 7-inch (17.8-cm) colour touch screen offers smooth, tablet-like interaction with customisable convenience and productivity apps.
- Front access to the paper path and power button means you'll virtually never have to access the back of the device, allowing placement in or on cabinets.
- Innovative serviceability features, starting with singledoor access to parts and supplies, help you resolve problems quickly.

Ready when you are

- Long-life fuser and imaging components extend uptime.
- Unison™ Toner replacement cartridges deliver up to 45,000 pages** of high-quality printing.
- Steel frame and durable design stands up to heavy use and harsh environments.


Full-spectrum security

- Lexmark's full-spectrum security architecture helps keep your information safe-in the document, on the device and over the network.
- Keypoint Intelligence Buyers Lab honoured Lexmark with a prestigious BLI PaceSetter award for Document Imaging Security***.



Built for planet earth

- Energy management features reduce power consumption in active use or sleep mode.
- Standard two-sided printing saves paper.
- Device is rated EPEAT® Gold and ENERGY STAR® certified.
- Recycle cartridges through the award-winning Lexmark Cartridge Collection Programme (LCCP).





Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.
**Average yield based on approximately 5% print coverage.
***Award based on North America and/or Western Europe data

Lexmark XM5370



- 1 Multifunction product with 7-inch (17.8 cm) class e-Task colour touch screen 29.1 x 22 x 22.8 inches 739.1 x 558.8 x 578.4 mm
- 2 100-sheet multipurpose feeder Dimensions included as part of base model
- 3 550-sheet tray
 Dimensions included as part of base model
- 4 550-sheet tray 4.3 x 16.85 x 20.1 inches 110 x 428 x 510 mm

- 5 2100-sheet tray 13.8 x 16.85 x 20.1 inches 350 x 428 x 510 mm
- 6 Castor base 5 x 20.5 x 27.3 inches 126 x 521 x 693 mm
- 7 250-sheet tray 3.2 x 16.85 x 20.1 inches 80 x 428 x 510 mm
- 8 550-sheet lockable tray 4.3 x 16.85 x 20.1 inches 110 x 428 x 510 mm

- 9 250-sheet lockable tray 3.2 x 16.85 x 20.1 inches 80 x 428 x 510 mm
- 10 Swivel cabinet 10.4 x 18.7 x 23.6 inches 263 x 476 x 600 mm
- 11 Adjustable printer stand 23 x 23.5 x 23.5 584.2 x 596.9 x 596.9
- 12 Spacer to add additional height 4.3 x 16.85 x 20.1 inches 110 x 428 x 510 mm



Note 1: Supports up to 3 optional 550-sheet trays; OR one optional 550-sheet tray and one optional 2100-sheet tray. For maximum paper input capacity, instal 1 optional 550-sheet tray and one optional 2100-sheet tray. When a 2100-sheet tray is installed, it must be the bottom tray, and a castor base is required.

Note 2: All measurements are shown as height x width x depth. For more information about supported configurations, refer to the Printer, Option and Stand Compatibility Guide at http://www.lexmark.com/publications/furniture_safety/

© 2018 Lexmark. All rights reserved.

Lexmark, the Lexmark logo and Unison are trademarks of Lexmark International, Inc., registered in the United States and/or other countries. AirPrint® and the AirPrint Logo® are trademarks of Apple, Inc. ENERGY STAR® is a U.S. registered mark. Google Cloud Print™ is a trademark of Google, Inc. MOPRIA®, the Mopria® Logo™ and the Mopria® Alliance logos are trademarks, service marks, and certification marks of Mopria Alliance, Inc. in the United States and other countries. All other trademarks are the property of their respective owners.

This product includes software developed by the OpenSSL Project for use in the Open SSL Toolkit (http://www.openssl.org/).



Stock & Label Guide. Media Sizes Supported 10 Envelope, 7 3/4 Envelope, 9 Envelope, A4, A5, B5 Envelope, C5 Envelope, DL Envelope, Executive, Folio, JIS-B5, Legal, Letter, Statement, Universal, Oficio, A6 General Information ⁴	Product specifications	Lexmark XM5370
Print Speed: Up to* Time to First Poges As fast as Time to First Poges As fast as Time to First Poges As fast as Black: 1200 Image Quality, 1200 x 1200 dp., 2400 Image Quality, 300 x 300 dpi, 600 x 600 dpi Memory / Processor Memory / Processor Memory / Processor Maximum Anothly Duty Cycle: Up to³ Stondard: 2048 MB / Maximum: 6144 MB / Quad Core, 1200 MHz Hard Disk Recommended Monthly Page Volume³ As 5000 - 100000 pages Maximum Monthly Duty Cycle: Up to³ Stondard: 350000 pages per month Copy Copy Copy Copy Copy Copy Copy Cop	Print	
Time to First Page: As fast as S Print Resolution	Display	Lexmark e-Task 7-inch (17.8 cm) colour touch screen
Time to First Page: As fast as S Print Resolution	. ,	
Memory / Processor		··
Hard Disk Recommended Monthly Page Volume ² S000 - 1000000 pages Recommended Monthly Duty Cycle: Up to¹ S0000 pages per month Copy Copy Copy Seed: Up to¹ Black: 46 cpm Black: 46 cpm Black: 46 cpm Standard Fype / ADF Scan Scanes Scane Scanes Scane Scanes Scane Flatbed scanner with ADF / DADF (single pass Duplex) Ad/Ltr Duplex Scan Speed: Up to / Duplex Scan Speed: Up to / Scan Speed: Up to / Duplex Scan Speed: Up to / Scan Speed: Up to / Duplex Scan Speed: Up to / Scan Speed: Up t	Print Resolution	Black: 1200 Image Quality, 1200 x 1200 dpi, 2400 Image Quality, 300 x 300 dpi, 600 x 600 dpi
Recommended Monthly Page Volume ² S000 - 100000 pages Maximum Monthly Duty Cycle: Up to ³ 350000 pages per month Copy Copy Copy Speed: Up to ⁴ Black: 66 cpm Time to First Copy: as fast as Black: 4.0 seconds Scan Scaner Type / ADF Scan Selow Floated Scanner with ADF / DADF (single pass Duplex) AA/Ltr Duplex: Scan Speed: Up to / Duplex Scan Speed: Up to / Scan Speed: Up	Memory / Processor	Standard: 2048 MB / Maximum: 6144 MB / Quad Core, 1200 MHz
Maximum Monthly Duty Cycle: Up to ¹ Copy Speed: Up to ⁴ Time to First Copy: as fast as Scana Scana Scana Scana Scana Scana Flotbed scanner with ADF / DADF (single pass Duplex) Ad/Itr Duplex Scan Speed: Up to / Scan	Hard Disk	Included in configuration
Copy Speed: Up to 6 Speed: Up to 6 Speed: Up to 6 Speed: Up to 7 Scanner Type / ADF Scan Scanner With ADF / DADF Scanner With Interpretation Scanner Type / ADF Scanner Ty	Recommended Monthly Page Volume ²	5000 - 100000 pages
Time to First Copy: as fast as Scane	Maximum Monthly Duty Cycle: Up to ³	350000 pages per month
Scanner Type / ADF Scan Scanner Type / ADF Scan Flottbed scanner with ADF / DADF (single pass Duplex) Ad/Ltr Duplex Scan Speed: Up to / Scan S	Сору	
Scane Scaner Type / ADF Scan Speed: Up to / Duplex Scan Speed: Up to / Spe	Copy Speed: Up to ⁶	Black: 66 cpm
Scanner Type / ADF Scan Speed: Up to / Duplex Scan Speed: Up to / Duplex Scan Speed: Up to / Duplex Scan Speed: Up to / Scan S	Time to First Copy: as fast as	Black: 4.0 seconds
Ad/Ltr Duplex Scan Speed: Up to / Duplex Scan Speed: Up to / Duplex Scan Speed: Up to / Scan Speed: Black: 72 / 75 sides per minute / Colour: 72 / 75 sides per minute / Duplex Scan Speed: Up to / Scan Speed	Scan	
Ad/Ltr Duplex Scan Speed: Up to / Duplex Scan Speed: Up to / Duplex Scan Speed: Up to / Scan Speed: Black: 72 / 75 sides per minute / Colour: 72 / 75 sides per minute / Duplex Scan Speed: Up to / Scan Speed	Scanner Type / ADF Scan	Flatbed scanner with ADF / DADF (single pass Duplex)
ADF Paper Input Capacity: Up to 200 pages 75 gsm bond Fax Modem Speed Max is 33,600 bps, V.34 Half-Duplex Kbps Supplies? Laser Cartridge Yields (up to) 45,000-page Extra High Yield Cartridge Imaging Unit Estimated Yield: Up to 150000 pages, based on 3 average letter/A4-size pages per print job and ~5% coverage Cartridge(S) Shipping with Product 11,000-page Starter Return Program Toner Cartridge Paper Handlling Included Paper Handling Included Paper Handling 550-Sheet Input, 100-Sheet Multipurpose Feeder, 550-Sheet Output Bin, Integrated Duplex Optional Paper Handling 250-Sheet Tray, 250-Sheet Tray, 250-Sheet Lockable Tray, 550-Sheet Lockable Tray Paper Input Capacity: Up to Standard: 650 pages 75 gsm bond / Maximum: 3300 pages 75 gsm bond Paper Output Capacity: Up to Standard: 650 pages 75 gsm bond / Maximum: 550 pages 75 gsm bond Media Types Supported Card Stock, Dual Web Labels, Envelopes, Integrated Labels, Paper Labels, Plain Paper, Transparencies, Refer to the Card Stock & Label Guide. Media Sizes Supported 10 Envelope, 7 3/4 Envelope, 9 Envelope, A4, A5, B5 Envelope, C5 Envelope, DL Envelope, Executive, Folio, JIS-B5, Legal, Letter, Statement, Universal, Oficio, A6 General Information Standard Ports 0ne Internal Card Slot, USB 2.0 Specification Hi-Speed Certified (Type B), Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified port (Type A), Two Rear USB 2.0 Specification Hi-Speed Certified port (Type A), Two Rear USB 2.0 Specification Hi-Speed Certified port (Type A), Two Rear USB 2.0 Specification Hi-Speed Certified port (Type A), Two Rear USB 2.0 Specification Hi-Speed Certified port (Type A), Two Rear USB 2.0 Specification Hi-Speed Certified port (Type A), Two Rear USB 2.0 Specification Hi-Speed Certified port (Type A), Two Rear USB 2.0 Specification Hi-Speed Certified port (Type A), Two Rear USB 2.0 Specification Hi-Speed Certified port (Type A), Two Rear USB 2.0 Specification Hi-Speed Certified port (Type A), Two Rear USB 2.0 Specification Hi-Speed Certified port (T	A4/Ltr Duplex Scan Speed: Up to / Duplex Scan	
Modem Speed		Black: 72 / 75 sides per minute / Colour: 72 / 75 sides per minute
Supplies? Loser Cartridge Yields (up to)¹	ADF Paper Input Capacity: Up to	200 pages 75 gsm bond
Loser Cartridge Yields (up to)' Loser Cartridge Yields (up to)' Imaging Unit Estimated Yield: Up to Inspire Handling Included Paper Handling Included	Fax	
Loser Cartridge Yields (up to)¹ A5,000-page Extra High Yield Cartridge Imaging Unit Estimated Yield: Up to 150000 pages, based on 3 average letter/A4-size pages per print job and ~ 5% coverage Cartridge(s) Shipping with Product¹ 11,000-page Starter Return Program Toner Cartridge Paper Handling Included Paper Handling Included Paper Handling 550-Sheet Input, 100-Sheet Multipurpose Feeder, 550-Sheet Output Bin, Integrated Duplex Optional Paper Handling 250-Sheet Tray, 550-Sheet Tray, 2100-Sheet Tray, 250-Sheet Lockable Tray, 550-Sheet Lockable Tray Paper Input Capacity: Up to Standard: 650 pages 75 gsm bond / Maximum: 3300 pages 75 gsm bond Paper Output Capacity: Up to Standard: 550 pages 75 gsm bond / Maximum: 550 pages 75 gsm bond Media Types Supported Card Stock, Dual Web Labels, Envelopes, Integrated Labels, Paper Labels, Plain Paper, Transparencies, Refer to the Card Stock & Label Guide. Media Sizes Supported 10 Envelope, 7 3/4 Envelope, 9 Envelope, A4, A5, B5 Envelope, C5 Envelope, DL Envelope, Executive, Folio, JIS-B5, Legal, Letter, Statement, Universal, Oficio, A6 General Information ⁴ Standard Ports One Internal Card Slot, USB 2.0 Specification Hi-Speed Certified (Type B), Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified ports (Type A), Two Rear USB 2.0 Specification Hi-Speed Certified ports (Type A), Two Rear USB 2.0 Specification Hi-Speed Certified ports (Type A), Two Rear USB 2.0 Specification Hi-Speed Certified ports (Type A), Two Rear USB 2.0 Specification Hi-Speed Certified ports (Type A), Two Rear USB 2.0 Specification Hi-Speed Certified ports (Type A), Two Rear USB 2.0 Specification Hi-Speed Certified ports (Type A), Two Rear USB 2.0 Specification Hi-Speed Certified ports (Type A), Two Rear USB 2.0 Specification Hi-Speed Certified ports (Type A), Two Rear USB 2.0 Specification Hi-Speed Certified ports (Type A), Two Rear USB 2.0 Specification Hi-Speed Certified ports (Type A), Two Rear USB 2.0 Specification Hi-Speed Certified ports (Type A), Tw	Modem Speed	Max is 33,600 bps, V.34 Half-Duplex Kbps
Imaging Unit Estimated Yield: Up to 150000 pages, based on 3 average letter/A4-size pages per print job and ~ 5% coverage Cartridge(s) Shipping with Product¹ 11,000-page Starter Return Program Toner Cartridge Paper Handling Included Paper Handling 550-Sheet Input, 100-Sheet Multipurpose Feeder, 550-Sheet Output Bin, Integrated Duplex Optional Paper Handling 250-Sheet Tray, 550-Sheet Tray, 250-Sheet Lockable Tray, 550-Sheet Lockable Tray Paper Input Capacity: Up to Standard: 650 pages 75 gsm bond / Maximum: 3300 pages 75 gsm bond Paper Output Capacity: Up to Standard: 550 pages 75 gsm bond / Maximum: 550 pages 75 gsm bond Media Types Supported Card Stock, Dual Web Labels, Envelopes, Integrated Labels, Paper Labels, Plain Paper, Transparencies, Refer to the Card Stock & Label Guide. Media Sizes Supported 10 Envelope, 7 3/4 Envelope, 9 Envelope, A4, A5, B5 Envelope, C5 Envelope, DL Envelope, Executive, Folio, JIS-B5, Legal, Letter, Statement, Universal, Oficio, A6 General Information4 Standard Ports One Internal Card Slot, USB 2.0 Specification Hi-Speed Certified (Type B), Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified port (Type A), Two Rear USB 2.0 Specification Hi-Speed Certified port (Type A), Two Rear USB 2.0 Specification Hi-Speed Certified port (Type A), Two Rear USB 2.0 Specification Hi-Speed Certified port (Type A), Two Rear USB 2.0 Specification Hi-Speed Certified port (Type A), Two Rear USB 2.0 Specification Hi-Speed Certified port (Type A), Two Rear USB 2.0 Specification Hi-Speed Certified port (Type A), Two Rear USB 2.0 Specification Hi-Speed Certified port (Type A), Two Rear USB 2.0 Specification Hi-Speed Certified port (Type A), Two Rear USB 2.0 Specification Hi-Speed Certified port (Type A), Two Rear USB 2.0 Specification Hi-Speed Certified port (Type A), Two Rear USB 2.0 Specification Hi-Speed Certified port (Type A), Two Rear USB 2.0 Specification Hi-Speed Certified port (Type A), Two Rear USB 2.0 Specification Hi-Speed Certified port (Type A), Two Rear U	Supplies ⁷	
Cartridge(s) Shipping with Product¹ 11,000-page Starter Return Program Toner Cartridge Paper Handling Included Paper Handling 550-Sheet Input, 100-Sheet Multipurpose Feeder, 550-Sheet Output Bin, Integrated Duplex Optional Paper Handling 250-Sheet Tray, 550-Sheet Tray, 250-Sheet Lockable Tray, 550-Sheet Lockable Tray Paper Input Capacity: Up to Standard: 650 pages 75 gsm bond / Maximum: 3300 pages 75 gsm bond Paper Output Capacity: Up to Standard: 550 pages 75 gsm bond / Maximum: 550 pages 75 gsm bond Media Types Supported Card Stock, Dual Web Labels, Envelopes, Integrated Labels, Paper Labels, Plain Paper, Transparencies, Refer to the Card Stock & Label Guide. Media Sizes Supported 10 Envelope, 7 3/4 Envelope, 9 Envelope, A4, A5, B5 Envelope, C5 Envelope, DL Envelope, Executive, Folio, JIS-B5, Legal, Letter, Statement, Universal, Oficio, A6 General Information4 Standard Ports 20 One Internal Card Slot, USB 2.0 Specification Hi-Speed Certified (Type B), Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified ports (Type A) Optional Network Ports / Optional Local Ports Internal MarkNet N8350 802.11b/g/n Wireless / Internal RS-232C serial, Internal 1284-B Bidirectional Parallel Noise Level: Operating Print: 57 dBA / Copy: 60 dBA / Scan: 56 dBA Specified Operating Environment Temperature: 16 to 32°C (60 to 90°F), Humidity: 8 to 80% Relative Humidity, Altitude: 0 - 2896 Meters (9,500 Feet) Product Warranty 1-Year Onsite Repair, Next Business Day	Laser Cartridge Yields (up to) ¹	45,000-page Extra High Yield Cartridge
Paper Handling Included Paper Handling S50-Sheet Input, 100-Sheet Multipurpose Feeder, 550-Sheet Output Bin, Integrated Duplex Optional Paper Handling 250-Sheet Tray, 550-Sheet Tray, 2100-Sheet Tray, 250-Sheet Lockable Tray, 550-Sheet Lockable Tray Paper Input Capacity: Up to Standard: 650 pages 75 gsm bond / Maximum: 3300 pages 75 gsm bond Paper Output Capacity: Up to Standard: 550 pages 75 gsm bond / Maximum: 550 pages 75 gsm bond Media Types Supported Card Stock, Dual Web Labels, Envelopes, Integrated Labels, Paper Labels, Plain Paper, Transparencies, Refer to the Card Stock & Label Guide. Media Sizes Supported 10 Envelope, 7 3/4 Envelope, 9 Envelope, A4, A5, B5 Envelope, C5 Envelope, DL Envelope, Executive, Folio, JIS-B5, Legal, Letter, Statement, Universal, Oficio, A6 General Information Standard Ports One Internal Card Slot, USB 2.0 Specification Hi-Speed Certified (Type B), Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified port (Type A), Two Rear USB 2.0 Specification Hi-Speed Certified ports (Type A) Optional Network Ports / Optional Local Ports Internal MarkNet N8350 802.11b/g/n Wireless / Internal RS-232C serial, Internal 1284-B Bidirectional Parallel Noise Level: Operating Print: 57 dBA / Copy: 60 dBA / Scan: 56 dBA Specified Operating Environment Temperature: 16 to 32°C (60 to 90°F), Humidity: 8 to 80% Relative Humidity, Altitude: 0 - 2896 Meters (9,500 Feet) Product Warranty 1-Year Onsite Repair, Next Business Day	Imaging Unit Estimated Yield: Up to	150000 pages, based on 3 average letter/A4-size pages per print job and ~ 5% coverage
Included Paper Handling 550-Sheet Input, 100-Sheet Multipurpose Feeder, 550-Sheet Output Bin, Integrated Duplex Optional Paper Handling 250-Sheet Tray, 550-Sheet Tray, 2100-Sheet Tray, 250-Sheet Lockable Tray, 550-Sheet Lockable Tray Paper Input Capacity: Up to Standard: 650 pages 75 gsm bond / Maximum: 3300 pages 75 gsm bond Paper Output Capacity: Up to Standard: 550 pages 75 gsm bond / Maximum: 550 pages 75 gsm bond Media Types Supported Card Stock, Dual Web Labels, Envelopes, Integrated Labels, Paper Labels, Plain Paper, Transparencies, Refer to the Card Stock & Label Guide. Media Sizes Supported 10 Envelope, 7 3/4 Envelope, 9 Envelope, A4, A5, B5 Envelope, C5 Envelope, DL Envelope, Executive, Folio, JIS-B5, Legal, Letter, Statement, Universal, Oficio, A6 General Information Standard Ports One Internal Card Slot, USB 2.0 Specification Hi-Speed Certified (Type B), Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified port (Type A), Two Rear USB 2.0 Specification Hi-Speed Certified ports (Type A) Optional Network Ports / Optional Local Ports Internal MarkNet N8350 802.11b/g/n Wireless / Internal RS-232C serial, Internal 1284-B Bidirectional Parallel Noise Level: Operating Print: 57 dBA / Copy: 60 dBA / Scan: 56 dBA Specified Operating Environment Temperature: 16 to 32°C (60 to 90°F), Humidity: 8 to 80% Relative Humidity, Altitude: 0 - 2896 Meters (9,500 Feet) Product Warranty	Cartridge(s) Shipping with Product ¹	11,000-page Starter Return Program Toner Cartridge
Optional Paper Handling 250-Sheet Tray, 550-Sheet Tray, 2100-Sheet Tray, 250-Sheet Lockable Tray, 550-Sheet Lockable Tray Paper Input Capacity: Up to Standard: 650 pages 75 gsm bond / Maximum: 3300 pages 75 gsm bond Paper Output Capacity: Up to Standard: 550 pages 75 gsm bond / Maximum: 550 pages 75 gsm bond Media Types Supported Card Stock, Dual Web Labels, Envelopes, Integrated Labels, Paper Labels, Plain Paper, Transparencies, Refer to the Card Stock & Label Guide. Media Sizes Supported 10 Envelope, 7 3/4 Envelope, 9 Envelope, A4, A5, B5 Envelope, C5 Envelope, DL Envelope, Executive, Folio, JIS-B5, Legal, Letter, Statement, Universal, Officio, A6 General Information Standard Ports One Internal Card Slot, USB 2.0 Specification Hi-Speed Certified (Type B), Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified port (Type A), Two Rear USB 2.0 Specification Hi-Speed Certified ports (Type A) Optional Network Ports / Optional Local Ports Noise Level: Operating Print: 57 dBA / Copy: 60 dBA / Scan: 56 dBA Specified Operating Environment Temperature: 16 to 32°C (60 to 90°F), Humidity: 8 to 80% Relative Humidity, Altitude: 0 - 2896 Meters (9,500 Feet) Product Warranty	Paper Handling	
Paper Input Capacity: Up to Standard: 650 pages 75 gsm bond / Maximum: 3300 pages 75 gsm bond Paper Output Capacity: Up to Standard: 550 pages 75 gsm bond / Maximum: 550 pages 75 gsm bond Media Types Supported Card Stock, Dual Web Labels, Envelopes, Integrated Labels, Paper Labels, Plain Paper, Transparencies, Refer to the Card Stock & Label Guide. Media Sizes Supported 10 Envelope, 7 3/4 Envelope, 9 Envelope, A4, A5, B5 Envelope, C5 Envelope, DL Envelope, Executive, Folio, JIS-B5, Legal, Letter, Statement, Universal, Oficio, A6 General Information Standard Ports One Internal Card Slot, USB 2.0 Specification Hi-Speed Certified (Type B), Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified port (Type A), Two Rear USB 2.0 Specification Hi-Speed Certified ports (Type A) Optional Network Ports / Optional Local Ports Internal MarkNet N8350 802.11b/g/n Wireless / Internal RS-232C serial, Internal 1284-B Bidirectional Parallel Noise Level: Operating Print: 57 dBA / Copy: 60 dBA / Scan: 56 dBA Specified Operating Environment Temperature: 16 to 32°C (60 to 90°F), Humidity: 8 to 80% Relative Humidity, Altitude: 0 - 2896 Meters (9,500 Feet) Product Warranty	Included Paper Handling	550-Sheet Input, 100-Sheet Multipurpose Feeder, 550-Sheet Output Bin, Integrated Duplex
Paper Output Capacity: Up to Standard: 550 pages 75 gsm bond / Maximum: 550 pages 75 gsm bond Media Types Supported Card Stock, Dual Web Labels, Envelopes, Integrated Labels, Paper Labels, Plain Paper, Transparencies, Refer to the Card Stock & Label Guide. Media Sizes Supported 10 Envelope, 7 3/4 Envelope, 9 Envelope, A4, A5, B5 Envelope, C5 Envelope, DL Envelope, Executive, Folio, JIS-B5, Legal, Letter, Statement, Universal, Oficio, A6 General Information Standard Ports One Internal Card Slot, USB 2.0 Specification Hi-Speed Certified (Type B), Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified port (Type A), Two Rear USB 2.0 Specification Hi-Speed Certified ports (Type A) Optional Network Ports / Optional Local Ports Internal MarkNet N8350 802.11b/g/n Wireless / Internal RS-232C serial, Internal 1284-B Bidirectional Parallel Noise Level: Operating Print: 57 dBA / Copy: 60 dBA / Scan: 56 dBA Specified Operating Environment Temperature: 16 to 32°C (60 to 90°F), Humidity: 8 to 80% Relative Humidity, Altitude: 0 - 2896 Meters (9,500 Feet) Product Warranty 1-Year Onsite Repair, Next Business Day	Optional Paper Handling	250-Sheet Tray, 550-Sheet Tray, 2100-Sheet Tray, 250-Sheet Lockable Tray, 550-Sheet Lockable Tray
Media Types Supported Card Stock, Dual Web Labels, Envelopes, Integrated Labels, Paper Labels, Plain Paper, Transparencies, Refer to the Card Stock & Label Guide. Media Sizes Supported 10 Envelope, 7 3/4 Envelope, 9 Envelope, A4, A5, B5 Envelope, C5 Envelope, DL Envelope, Executive, Folio, JIS-B5, Legal, Letter, Statement, Universal, Oficio, A6 General Information Standard Ports One Internal Card Slot, USB 2.0 Specification Hi-Speed Certified (Type B), Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified port (Type A), Two Rear USB 2.0 Specification Hi-Speed Certified ports (Type A) Optional Network Ports / Optional Local Ports Noise Level: Operating Print: 57 dBA / Copy: 60 dBA / Scan: 56 dBA Specified Operating Environment Temperature: 16 to 32°C (60 to 90°F), Humidity: 8 to 80% Relative Humidity, Altitude: 0 - 2896 Meters (9,500 Feet) Product Warranty	Paper Input Capacity: Up to	Standard: 650 pages 75 gsm bond / Maximum: 3300 pages 75 gsm bond
Stock & Label Guide. Media Sizes Supported 10 Envelope, 7 3/4 Envelope, 9 Envelope, A4, A5, B5 Envelope, C5 Envelope, DL Envelope, Executive, Folio, JIS-B5, Legal, Letter, Statement, Universal, Oficio, A6 General Information ⁴ Standard Ports One Internal Card Slot, USB 2.0 Specification Hi-Speed Certified (Type B), Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified port (Type A), Two Rear USB 2.0 Specification Hi-Speed Certified ports (Type A) Optional Network Ports / Optional Local Ports Internal MarkNet N8350 802.11b/g/n Wireless / Internal RS-232C serial, Internal 1284-B Bidirectional Parallel Noise Level: Operating Print: 57 dBA / Copy: 60 dBA / Scan: 56 dBA Specified Operating Environment Temperature: 16 to 32°C (60 to 90°F), Humidity: 8 to 80% Relative Humidity, Altitude: 0 - 2896 Meters (9,500 Feet) Product Warranty 1-Year Onsite Repair, Next Business Day	Paper Output Capacity: Up to	Standard: 550 pages 75 gsm bond / Maximum: 550 pages 75 gsm bond
General Information ⁴ Standard Ports One Internal Card Slot, USB 2.0 Specification Hi-Speed Certified (Type B), Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified ports (Type A), Two Rear USB 2.0 Specification Hi-Speed Certified ports (Type A) Optional Network Ports / Optional Local Ports Internal MarkNet N8350 802.11b/g/n Wireless / Internal RS-232C serial, Internal 1284-B Bidirectional Parallel Print: 57 dBA / Copy: 60 dBA / Scan: 56 dBA Specified Operating Environment Temperature: 16 to 32°C (60 to 90°F), Humidity: 8 to 80% Relative Humidity, Altitude: 0 - 2896 Meters (9,500 Feet) Product Warranty 1-Year Onsite Repair, Next Business Day	Media Types Supported	Card Stock, Dual Web Labels, Envelopes, Integrated Labels, Paper Labels, Plain Paper, Transparencies, Refer to the Card Stock & Label Guide.
Standard Ports One Internal Card Slot, USB 2.0 Specification Hi-Speed Certified (Type B), Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified ports (Type A), Two Rear USB 2.0 Specification Hi-Speed Certified ports (Type A) Optional Network Ports / Optional Local Ports Internal MarkNet N8350 802.11b/g/n Wireless / Internal RS-232C serial, Internal 1284-B Bidirectional Parallel Noise Level: Operating Print: 57 dBA / Copy: 60 dBA / Scan: 56 dBA Specified Operating Environment Temperature: 16 to 32°C (60 to 90°F), Humidity: 8 to 80% Relative Humidity, Altitude: 0 - 2896 Meters (9,500 Feet) Product Warranty 1-Year Onsite Repair, Next Business Day	Media Sizes Supported	10 Envelope, 7 3/4 Envelope, 9 Envelope, A4, A5, B5 Envelope, C5 Envelope, DL Envelope, Executive, Folio, JIS-B5, Legal, Letter, Statement, Universal, Oficio, A6
Optional Network Ports / Optional Local Ports Internal MarkNet N8350 802.11b/g/n Wireless / Internal RS-232C serial, Internal 1284-B Bidirectional Parallel Noise Level: Operating Print: 57 dBA / Copy: 60 dBA / Scan: 56 dBA Specified Operating Environment Temperature: 16 to 32°C (60 to 90°F), Humidity: 8 to 80% Relative Humidity, Altitude: 0 - 2896 Meters (9,500 Feet) Product Warranty 1-Year Onsite Repair, Next Business Day	General Information⁴	
Optional Network Ports / Optional Local Ports Internal MarkNet N8350 802.11b/g/n Wireless / Internal RS-232C serial, Internal 1284-B Bidirectional Parallel Noise Level: Operating Print: 57 dBA / Copy: 60 dBA / Scan: 56 dBA Specified Operating Environment Temperature: 16 to 32°C (60 to 90°F), Humidity: 8 to 80% Relative Humidity, Altitude: 0 - 2896 Meters (9,500 Feet) Product Warranty 1-Year Onsite Repair, Next Business Day	Standard Ports	One Internal Card Slot, USB 2.0 Specification Hi-Speed Certified (Type B), Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified port (Type A), Two Rear USB 2.0 Specification Hi-Speed Certified ports (Type A)
Specified Operating Environment Temperature: 16 to 32°C (60 to 90°F), Humidity: 8 to 80% Relative Humidity, Altitude: 0 - 2896 Meters (9,500 Feet) Product Warranty 1-Year Onsite Repair, Next Business Day	Optional Network Ports / Optional Local Ports	
Product Warranty 1-Year Onsite Repair, Next Business Day	Noise Level: Operating	Print: 57 dBA / Copy: 60 dBA / Scan: 56 dBA
	Specified Operating Environment	Temperature: 16 to 32°C (60 to 90°F), Humidity: 8 to 80% Relative Humidity, Altitude: 0 - 2896 Meters (9,500 Feet)
Size (mm - H x W x D) / Weight 739.1 x 558.8 x 578.4 mm / 44.1 kg	Product Warranty	1-Year Onsite Repair, Next Business Day
	Size (mm - H x W x D) / Weight	739.1 x 558.8 x 578.4 mm / 44.1 kg

All information in this brochure is subject to change without notice. Lexmark is not liable for any errors or omissions. MX721 also available with standard hard drive.

This is a Class A device according to international electromagnetic emissions standards (i.e. FCC Rules, EN 55022/EN 55032, etc.). Class A products are intended for use in non-residential/non-domestic environments. Use of a Class A product in residential/domestic environments may cause interference to radio communications and require corrective measures.



Advanced Print Scan Solutions

Unit 3 / 74 Thomsons Rd Keilor Park Victoria 3042 1300 226 995 www.apssolutions.com.au

'Average yield at approximately 5% print coverage per colour. 2"Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage. 3"Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs. 4Printers are sold subject to certain license/agreement conditions. See www.lexmark.com/printerlicense for details. 5Actual Yield may vary based on other factors such as device speed, paper size and feed orientation, toner coverage, tray source, percentage of black-only printing and average print job complexity. 6Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds. 7Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/regions for more details.

